

SPECIFICATION SHEET

171505

Acrylic Shower Base

General Specifications:

FEATURES:


- Ready to Install
- 3 Sided - Tile Flange for Water Protection
- One Piece Construction

MATERIAL:

- High-grade Acrylic with Fiberglass Reinforcement

CODE STANDARDS:

- CSA B45.5/IAPMO Z124



Technical Information:

| | | | |
|-------------------------|--|----------------------|-------|
| Material: | High-grade Acrylic with Fiberglass Reinforcement | Finish Color: | White |
| Installed Size: | Approx. 36 x 42 x 5.5 in (914 x 1067 x 140 mm) | | |
| Floor Footprint: | Approx. 36 x 42 in (914 x 1067 mm) | | |
| Drain Location: | Centered | | |
| Drain Hole: | 3.35" (85 mm) | | |
| Installation: | 3 Wall Alcove | | |
| Threshold: | 36" Single 3.94" h (914 x 100 mm) | | |
| Tile Flange: | 1.18" (30 mm) | | |
| Surface: | Nonslip Textured | | |

Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standards Z124.1.2-2005.

NOTES:

- The Sub-floor is required to be within 1/2" of level from end to end.
- Measure the actual product for rough-in details before you start your installation.
- Install this product using basic industry standards.

IMPORTANT:

- These measurements are subject to change. No responsibility is assumed for use of superseded or voided leaflet.

