

SPECIFICATION SHEET

172058 - Nantucket

Oval Acrylic Luxury Bathtub

General Specifications:

FEATURES:

■ Floor or Wall Mount Faucet options

MATERIAL:

• High-grade acrylic with fiberglass reinforcement

CODE STANDARDS:

CSA B45.5-11/IAPMO Z124



Technical Information:

| Installed Size: | Approx. 70.75 x 33.5 x 30.25 in (1800 x 850 x 770 mm) |
|---------------------------------|---|
| Floor Footprint: | Approx. 48.0 x 20.5 in (1220 x 520 mm) |
| Drain Location: | Side |
| Weight: | 87.12 lb (39.5 kg) |
| Weight With Water: | 499.5 lb (227 kg) |
| Gallons To Overflow: | 49.4 Gallons (187 L) |
| Bathing Well At Sump: | 42.5 x 13.8/17.3 in (1080 x 350/440 mm) |
| Bathing Well At Rim: | 63.0 x 20.5/26.4 in (1600 x 520/670 mm) |
| Water Depth To Overflow: | 14.96 in (380 mm) |
| Floor Loading (Project Area): | 73.1 lb per sq/ft (357 kg per sq/m) |
| Backrest Angle (From Vertical): | 45°/18° |

Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standards Z124.1.2-2005.

NOTES:

- Refer to the installation instructions supplied with this product for additional information.
- Provide suitable reinforcement for all supports.

IMPORTANT:

• These measurements are subject to change. No responsibility is assumed for use of superseded or voided leaflet.



Interquatic:



