

SPECIFICATION SHEET

172036 - Hudson

Oval Acrylic Luxury Bathtub

General Specifications:

FEATURES:

- Floor or Wall Mount Faucet Required
- 70.5" (1790 mm) x 32.75" (830 mm) x 28.25" (720 mm)

MATERIAL:

• High-grade acrylic with fiberglass reinforcement

CODE STANDARDS:

CSA B45.5-11/IAPMO Z124



Technical Information:

| Installed size: | Approx. 70.5" X 32.75 X 28.25 in. (1790 x 830 x 720 mm) |
|---------------------------------|---|
| Floor footprint: | Approx. 49.5 x 25.25 in. (1260 x 640 mm) |
| Drain location: | Center |
| Weight: | 94.8 lb (43 kg) |
| Weight with water: | 590.5 lb (268 kg) |
| Gallons to overflow: | 59.4 Gallons (225 L) |
| Bathing well at sump: | 44.1 x 18.9 in. (1120 x 480 mm) |
| Bathing well at rim: | 68.1 x 30.3 in.(1730 x 770 mm) |
| Water depth to overflow: | 14.76 in. (375 mm) |
| Floor loading (project area): | 68.0 lbs per sq/ft (332 kg per sq/m) |
| Backrest angle (from Vertical): | 32° |

Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standards Z124.1.2-2005.

NOTES:

- Refer to the installation instructions supplied with this product for additional information.
- Provide suitable reinforcement for all supports.

IMPORTANT:

• These measurements are subject to change. No responsibility is assumed for use of superseded or voided leaflet.



Interquatic:



